

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
25 November 2004 (25.11.2004)

PCT

(10) International Publication Number
WO 2004/102511 A1

(51) International Patent Classification⁷: G09F 13/18,
13/06

(21) International Application Number:
PCT/SE2004/000523

(22) International Filing Date: 5 April 2004 (05.04.2004)

(25) Filing Language: Swedish

(26) Publication Language: English

(30) Priority Data:
0300995-8 3 April 2003 (03.04.2003) SE

(71) Applicant and

(72) Inventor: KARLSSON, Dennis [SE/SE]; PL. 1153 Hol,
S-441 93 ALINGSÅS (SE).

(74) Agents: KYLIN, Peter et al.; Hynell Patenttjänst AB, Pa-
tron Carls väg 2, S-683 40 HAGFORS/UDDEHOLM (SE).

(81) Designated States (unless otherwise indicated, for every
kind of national protection available): AE, AG, AL, AM,

AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN,
CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI,
GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE,
KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD,
MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG,
PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM,
TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM,
ZW.


(84) Designated States (unless otherwise indicated, for every
kind of regional protection available): ARIPO (BW, GH,
GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW),
Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), Euro-
pean (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR,
GB, GR, HU, IE, IT, LU, MC, NL, PL, PT, RO, SE, SI, SK,
TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW,
ML, MR, NE, SN, TD, TG).

Published:

— with international search report

For two-letter codes and other abbreviations, refer to the "Guid-
ance Notes on Codes and Abbreviations" appearing at the begin-
ning of each regular issue of the PCT Gazette.

(54) Title: METHOD FOR PRODUCTION OF ELECTRIC SIGNS AND AN ELECTRIC SIGN



(57) Abstract: A method for producing, by a laser that scans the rear side of a transparent object, figures and text that are recessed in the transparent material and that as seen from the outside (5) appear as a raised relief (1) and for which the effect of depth (d , d') depends on the amplitude of a signal superposed the input, frequency-controlled laser power by which the screen pattern is obtained. By an optimal fineness of scanning relative the material of the sign, the figures may obtain a very strong luminescence even at a very low input edge-illumination power. Furthermore, the invention relates to an edge-illuminated electric sign (L1, L2) with a figure produced by the manufacturing method according to the invention. Furthermore, the invention relates to a mounting system in the form of two interacting moulding strips (3, 4) for mounting one or more electric signs (L1, L2) manufactured according to the invention.

WO 2004/102511 A1